

Package: templr (via r-universe)

October 12, 2026

Type Package

Title MASCOTNUM / RT-UQ Algorithms Template Tools

Version 0.2-4.1

Date 2026-08-26

Author Yann Richet [aut, cre]

([<https://orcid.org/0000-0002-5677-8458>](https://orcid.org/0000-0002-5677-8458))

Maintainer Yann Richet <yann.richet@asn.fr>

Description Helper functions for MASCOTNUM / RT-UQ

<<https://uq.math.cnrs.fr/>> algorithm template, for design of
numerical experiments practice: algorithm template parser to
support MASCOTNUM specification

<<https://github.com/MASCOTNUM/algorithms>>, 'ask & tell'
decoupling injection (inspired by

<<https://search.r-project.org/CRAN/refmans/sensitivity/html/decoupling.html>>)
to use ``crimped" algorithms (like uniroot(), optim(), ...) from
outside R, basic template examples: Brent algorithm for 1 dim
root finding and L-BFGS-B from base optim().

License Apache License (>= 2)

Encoding UTF-8

Depends R (>= 4.0)

Imports utils, stats, remotes, xml2, jsonlite

Suggests testthat, future, mco, praise, curl

URL <https://github.com/MASCOTNUM/templr>

Config/roxygen2/version 8.0.0

Config/pak/sysreqs git libxml2-dev

Repository <https://rt-uq.r-universe.dev>

Date/Publication 2026-08-28 21:36:50 UTC

RemoteUrl <https://github.com/rt-uq/templr>

RemoteRef HEAD

RemoteSha 6b405400d8ee5a28407659f260c89421c424e76f

Contents

ask_dX	2
ask_dY	3
ask_X	5
ask_Y	6
from01	8
import	8
list.results	9
max_input	10
min_input	10
parse.algorithm	11
read.algorithm	11
run.algorithm	12
tell_dY	13
tell_Y	14
to01	15
Index	16

ask_dX	<i>ask&tell component function to 'ask' where objective function gradient evaluation is required.</i>
--------	---

Description

ask&tell component function to 'ask' where objective function gradient evaluation is required.

Usage

```
ask_dX(  
  id = 0,  
  dX.tmp = "dX.todo",  
  tmp_path = file.path(tempdir(), "..", "asktell.tmp"),  
  sleep_step = 0.1,  
  sleep_init = 0,  
  timeout = 360000,  
  trace = function(...) cat(paste0(..., "\n")),  
  clean = TRUE  
)
```

Arguments

id	unique identifier for this asktell loop (default: "0")
dX.tmp	temporary "X" values file (default: "dX.todo")
tmp_path	temporary directory to store X.tmp & Y.tmp (default: 'tempdir()/../asktell.tmp')
sleep_step	delay between checking X.tmp and Y.tmp (default: 0.1 sec.)

sleep_init	initial delay before checking X.tmp and Y.tmp (default: 0 sec.)
timeout	maximum delay before breaking loop if X.tmp or Y.tmp doesn't appear (default: 360000 sec. = 100 h.) .
trace	function to display asktell loop status (default : 'cat')
clean	should we cleanup temporary files after reading ? (default: TRUE)

Details

'ask&tell' injection loop to call an external objective function within an inline algorithm (like optim(...)) Main idea: pass 'ask_Y' as objective function argument of algorithm, which will wait until you call 'tell_Y' in another R process. In this secondary process, you can read what X is called using 'ask_X', and when you know what values returns from the external objective, just call 'tell_Y' to give it.

Value

input values of objective function to compute externally

Author(s)

Y. Richet, discussions with D. Sinoquet. Async IO principle was defined by G. Pujol.

Examples

```
## Not run: ### Assumes you can use two independent R sessions
## In main R session
ask_dY(x=123)
## In another R session
ask_dX() # returns 123
tell_dY(y=456)
## Then ask_dY in main R session returns with value '456'

## End(Not run)
```

ask_dY	<i>ask&tell component function to 'ask' objective function gradient evaluation using finite difference.</i>
--------	---

Description

ask&tell component function to 'ask' objective function gradient evaluation using finite difference.

Usage

```
ask_dY(
  x,
  dX = 0.001,
  id = 0,
  dX.tmp = "dX.todo",
  dY.tmp = "dY.done",
  tmp_path = file.path(tempdir(), "..", "asktell.tmp"),
  sleep_step = 0.1,
  sleep_init = 0,
  timeout = 360000,
  trace = function(...) cat(paste0(..., "\n")),
  clean = TRUE,
  force_cleanup = FALSE
)
```

Arguments

x	input values of objective function gradient to compute
dX	finite difference applied to input values to compute gradient
id	unique identifier for this asktell loop (default: "0")
dX.tmp	temporary "X" values file (default: "dX.todo")
dY.tmp	temporary "Y" values file (default: "dY.done")
tmp_path	temporary directory to store X.tmp & Y.tmp (default: 'tempdir()/../asktell.tmp')
sleep_step	delay between checking X.tmp and Y.tmp (default: 0.1 sec.)
sleep_init	initial delay before checking X.tmp and Y.tmp (default: 0 sec.)
timeout	maximum delay before breaking loop if X.tmp or Y.tmp doesn't appear (default: 360000 sec. = 100 h.) .
trace	function to display asktell loop status (default : 'cat')
clean	should we cleanup temporary files after reading ? (default: TRUE)
force_cleanup	should we cleanup temporary files before writing (possible conflicting asktell calls) ? (default: FALSE)

Details

'ask&tell' injection loop to call an external objective function within an inline algorithm (like optim(...)) Main idea: pass 'ask_Y' as objective function argument of algorithm, which will wait until you call 'tell_Y' in another R process. In this secondary process, you can read what X is called using 'ask_X', and when you know what values returns from the external objective, just call 'tell_Y' to give it.

Value

output value of objective function gradient, as given by tell_dY() call in parallel session

Author(s)

Y. Richet, discussions with D. Sinoquet. Async IO principle was defined by G. Pujol.

Examples

```
## Not run:  ### Assumes you can use two independent R sessions
## In main R session
ask_dY(x=123)
## In another R session
ask_dX() # returns 123
tell_dY(y=456)
## Then ask_dY in main R session returns with value '456'

## End(Not run)
```

ask_X	<i>ask&tell component function to 'ask' where objective function evaluation is required.</i>
-------	--

Description

ask&tell component function to 'ask' where objective function evaluation is required.

Usage

```
ask_X(
  id = 0,
  X.tmp = "X.todo",
  tmp_path = file.path(tempdir(), "..", "asktell.tmp"),
  sleep_step = 0.1,
  sleep_init = 0.1,
  timeout = 360000,
  trace = function(...) cat(paste0(..., "\n")),
  clean = TRUE
)
```

Arguments

id	unique identifier for this asktell loop (default: "0")
X.tmp	temporary "X" values file (default: "X.todo")
tmp_path	temporary directory to store X.tmp & Y.tmp (default: 'tempdir()/../asktell.tmp')
sleep_step	delay between checking X.tmp and Y.tmp (default: 0.1 sec.)
sleep_init	initial delay before checking X.tmp and Y.tmp (default: 0 sec.)
timeout	maximum delay before breaking loop if X.tmp or Y.tmp doesn't appear (default: 360000 sec. = 100 h.) .
trace	function to display asktell loop status (default : 'cat')
clean	should we cleanup temporary files after reading ? (default: TRUE)

Details

'ask&tell' injection loop to call an external objective function within an inline algorithm (like optim(...)) Main idea: pass 'ask_Y' as objective function argument of algorithm, which will wait until you call 'tell_Y' in another R process. In this secondary process, you can read what X is called using 'ask_X', and when you know what values returns from the external objective, just call 'tell_Y' to give it.

Value

input value of objective function to compute externally

Author(s)

Y. Richet, discussions with D. Sinoquet. Async IO principle was defined by G. Pujol.

Examples

```
## Not run:  ### Assumes you can use two independent R sessions
## In main R session
  ask_Y(x=123)
## In another R session
  ask_X() # returns 123
  tell_Y(y=456)
## Then ask_dY in main R session returns with value '456'

## End(Not run)
```

ask_Y

ask&tell component function to 'ask' objective function evaluation.

Description

ask&tell component function to 'ask' objective function evaluation.

Usage

```
ask_Y(
  x,
  id = 0,
  X.tmp = "X.todo",
  Y.tmp = "Y.done",
  tmp_path = file.path(tempdir(), "..", "asktell.tmp"),
  sleep_step = 0.1,
  sleep_init = 0,
  timeout = 360000,
  trace = function(...) cat(paste0(..., "\n")),
  clean = TRUE,
  force_cleanup = FALSE
)
```

Arguments

x	input values of objective function to compute
id	unique identifier for this asktell loop (default: "0")
X.tmp	temporary "X" values file (default: "X.todo")
Y.tmp	temporary "Y" values file (default: "Y.done")
tmp_path	temporary directory to store X.tmp & Y.tmp (default: 'tempdir()/../asktell.tmp')
sleep_step	delay between checking X.tmp and Y.tmp (default: 0.1 sec.)
sleep_init	initial delay before checking X.tmp and Y.tmp (default: 0 sec.)
timeout	maximum delay before breaking loop if X.tmp or Y.tmp doesn't appear (default: 360000 sec. = 100 h.) .
trace	function to display asktell loop status (default : 'cat')
clean	should we cleanup temporary files after reading ? (default: TRUE)
force_cleanup	should we cleanup temporary files before writing (possible conflicting asktell calls) ? (default: FALSE)

Details

'ask&tell' injection loop to call an external objective function within an inline algorithm (like optim(...)) Main idea: pass 'ask_Y' as objective function argument of algorithm, which will wait until you call 'tell_Y' in another R process. In this secondary process, you can read what X is called using 'ask_X', and when you know what values returns from the external objective, just call 'tell_Y' to give it.

Value

output value of objective function, as given by tell_Y() call in parallel session

Author(s)

Y. Richet, discussions with D. Sinoquet. Async IO principle was defined by G. Pujol.

Examples

```
## Not run:  ### Assumes you can use two independent R sessions
## In main R session
ask_Y(x=123)
## In another R session
ask_X() # returns 123
tell_Y(y=456)
## Then ask_Y in main R session returns with value '456'

## End(Not run)
```

from01	<i>Helper function to scale from [0,1] to [min,max]</i>
--------	---

Description

Helper function to scale from [0,1] to [min,max]

Usage

```
from01(X, inp)
```

Arguments

X	values to scale
inp	list containing 'min' and 'max' values

Value

X scaled in [inp\$min, inp\$max]

Examples

```
from01(data.frame(x=matrix(runif(10))),list(x=list(min=10,max=20)))
```

import	<i>Dependencies loader, supports many protocols like github:, gitlab:, ... using remotes::instal_... Will create a local '.lib' directory to store packages installed</i>
--------	---

Description

Dependencies loader, supports many protocols like github:, gitlab:, ... using remotes::instal_... Will create a local '.lib' directory to store packages installed

Usage

```
import(
  ...,
  lib.loc = NULL,
  force = FALSE,
  trace = function(...) cat(paste0(..., "\n"))
)
```

Arguments

<code>...</code>	dependencies/libraries/packages to load
<code>lib.loc</code>	use to setup a dedicated libPath directory to install packages
<code>force</code>	if TRUE, (re)install the package even if a version is already loadable, overwriting any previous install
<code>trace</code>	display info

Value

(list of) load status of packages (TRUE/FALSE)

Examples

```
if(interactive()){
  import('VGAM')
}
```

list.results	<i>Parse algorithm string result in R list</i>
--------------	--

Description

Parse algorithm string result in R list

Usage

```
list.results(result)
```

Arguments

result	templated algorithm result string
--------	-----------------------------------

Value

list of string parsed: extract XML or JSON content

Examples

```
list.results(paste0(
  "<HTML name='minimum'>minimum is 0.523431237543406 found at ...</HTML>",
  "<min> 0.523431237543406 </min>",
  "<argmin>[ 0.543459029033452,0.173028395040855 ]</argmin>"))
```

max_input	<i>Helper function to get \$max from 'input' list</i>
-----------	---

Description

Helper function to get \$max from 'input' list

Usage

```
max_input(inp)
```

Arguments

inp	lst of objects containing 'max' field (as list)
-----	---

Value

array of inp\$...\$max values

Examples

```
max_input(list(x1=list(min=0,max=1),x2=list(min=2,max=3)))
```

min_input	<i>Helper function to get \$min from 'input' list</i>
-----------	---

Description

Helper function to get \$min from 'input' list

Usage

```
min_input(inp)
```

Arguments

inp	lst of objects containing 'min' field (as list)
-----	---

Value

array of inp\$...\$min values

Examples

```
min_input(list(x1=list(min=0,max=1),x2=list(min=2,max=3)))
```

parse.algorithm	<i>Parse algorithm file and returns its (header) indos and methods</i>
-----------------	--

Description

Parse algorithm file and returns its (header) indos and methods

Usage

```
parse.algorithm(file)
```

Arguments

file	Template algorithm file to parse
------	----------------------------------

Value

list of header infos and environment containing methods <constructor>,getInitialDesign,getNextDesign,displayResults

Examples

```
parse.algorithm(system.file("Brent.R", package="templr"))
```

read.algorithm	<i>Read algorithm file and returns one header info</i>
----------------	--

Description

Read algorithm file and returns one header info

Usage

```
read.algorithm(file, info = "help")
```

Arguments

file	Template algorithm file to read
info	header info to return

Value

list of header infos

Examples

```
read.algorithm(system.file("Brent.R", package="templr"),"help")
```

run.algorithm

*Apply a template algorithm file to an objective function***Description**

Apply a template algorithm file to an objective function

Usage

```
run.algorithm(
  algorithm_file,
  objective_function,
  input,
  output = NULL,
  options = NULL,
  work_dir = ".",
  overwrite = TRUE,
  trace = function(...) cat(paste0(..., "\n")),
  silent = FALSE,
  save_data = TRUE
)
```

Arguments

algorithm_file	templated algorithm file
objective_function	function to apply algorithm on
input	list of input arguments of function (eg. list(x1=list(min=0,max=1),x2=list(min=10,max=20)))
output	list of output names
options	algorithm options to overload default ones
work_dir	working directory to run algorithm. will store output files, images, ..
overwrite	if FALSE, stop with an error when work_dir already contains saved data (.Rds) from a previous run instead of silently overwriting it (default: TRUE)
trace	display running info
silent	quietness
save_data	enable (by default) saving of data (in .Rds) along algorithm iterations.

Value

algorithm result (and algorithm object & files as attributes)

Examples

```
run.algorithm(
  system.file("Brent.R", package="templr"),
  function(x) sin(x)-0.75,
  list(x=list(min=0,max=pi/2)),
  work_dir=tempdir()
)
```

tell_dY	<i>ask&tell component function to 'tell' objective function value to waiting 'ask_Y' call in another R session.</i>
---------	---

Description

ask&tell component function to 'tell' objective function value to waiting 'ask_Y' call in another R session.

Usage

```
tell_dY(
  dy,
  id = 0,
  dY.tmp = "dY.done",
  tmp_path = file.path(tempdir(), "..", "asktell.tmp"),
  trace = function(...) cat(paste0(..., "\n")),
  force_cleanup = FALSE
)
```

Arguments

dy	output value of objective function gradient to return
id	unique identifier for this asktell loop (default: "0")
dY.tmp	temporary "Y" values file (default: "dY.done")
tmp_path	temporary directory to store X.tmp & Y.tmp (default: 'tempdir()/../asktell.tmp')
trace	function to display asktell loop status (default : 'cat')
force_cleanup	should we cleanup temporary files before writing (possible conflicting asktell calls) ? (default: FALSE)

Details

'ask&tell' injection loop to call an external objective function within an inline algorithm (like optim(...)) Main idea: pass 'ask_Y' as objective function argument of algorithm, which will wait until you call 'tell_Y' in another R process. In this secondary process, you can read what X is called using 'ask_X', and when you know what values returns from the external objective, just call 'tell_Y' to give it.

Value

input value of objective function to compute externally

Author(s)

Y. Richet, discussions with D. Sinoquet. Async IO principle was defined by G. Pujol.

Examples

```
## Not run: ### Assumes you can use two independent R sessions
## In main R session
ask_dY(x=123)
## In another R session
ask_dX() # returns c(123, 123.123)
tell_dY(dy=c(456,456.123))
## Then ask_dY in main R session returns with value '1'

## End(Not run)
```

tell_Y	<i>ask&tell component function to 'tell' objective function value to waiting 'ask_Y' call in another R session.</i>
--------	---

Description

ask&tell component function to 'tell' objective function value to waiting 'ask_Y' call in another R session.

Usage

```
tell_Y(
  y,
  id = 0,
  Y.tmp = "Y.done",
  tmp_path = file.path(tempdir(), "..", "asktell.tmp"),
  trace = function(...) cat(paste0(..., "\n")),
  force_cleanup = FALSE
)
```

Arguments

y	output value of objective function to return
id	unique identifier for this asktell loop (default: "0")
Y.tmp	temporary "Y" values file (default: "Y.done")
tmp_path	temporary directory to store X.tmp & Y.tmp (default: 'tempdir()/../asktell.tmp')
trace	function to display asktell loop status (default : 'cat')
force_cleanup	should we cleanup temporary files before writing (possible conflicting asktell calls) ? (default: FALSE)

Details

'ask&tell' injection loop to call an external objective function within an inline algorithm (like optim(...)) Main idea: pass 'ask_Y' as objective function argument of algorithm, which will wait until you call 'tell_Y' in another R process. In this secondary process, you can read what X is called using 'ask_X', and when you know what values returns from the external objective, just call 'tell_Y' to give it.

Value

input value of objective function to compute externally

Author(s)

Y. Richet, discussions with D. Sinoquet. Async IO principle was defined by G. Pujol.

Examples

```
## Not run:  ### Assumes you can use two independent R sessions
## In main R session
  ask_Y(x=123)
## In another R session
  ask_X() # returns 123
  tell_Y(y=456)
## Then ask_dY in main R session returns with value '456'

## End(Not run)
```

to01

*Helper function to scale from [min,max] to [0,1]***Description**

Helper function to scale from [min,max] to [0,1]

Usage

```
to01(X, inp)
```

Arguments

X	values to scale
inp	list containing 'min' and 'max' values

Value

X scaled in [0,1]

Examples

```
to01(10+10*data.frame(x=matrix(runif(10))),list(x=list(min=10,max=20)))
```

Index

ask_dX, [2](#)
ask_dY, [3](#)
ask_X, [5](#)
ask_Y, [6](#)

from01, [8](#)

import, [8](#)

list.results, [9](#)

max_input, [10](#)
min_input, [10](#)

parse.algorithm, [11](#)

read.algorithm, [11](#)
run.algorithm, [12](#)

tell_dY, [13](#)
tell_Y, [14](#)
to01, [15](#)